



AllTape Supplies

Technical Data Sheet



AllTape Supplies

ATS - All Tape Supplies B.V.

Emma Goldmanweg 10 – 5032 MN – TILBURG – The Netherlands

Tel : +31 (0)13 3030800 (general)

Tel : +31 (0)13 3030811 (Personal Assistant)

Fax : +31 (0)13 3030801

www.alltape.eu




SCP499RS Masking Tapes

KEY FEATURES

- This is an edge reinforcement tape in the veneer splicing industry
- It can be used in combination with Fisher+Rueckle Edgemaster veneering reinforcement machines
- The product is standard available in spoolwound rolls in the size 6 mm x 3,000 meters on a 3 inch core
- Reinforcing of the sides of veneer sheets

CARRIER AND ADHESIVE



1. Crepe paper carrier
2. Natural rubber adhesive

TECHNICAL DETAILS

| Properties | Value |
|---------------------|-------------------|
| Total thickness | 150 micron |
| Adhesion to steel | 7,5 N/cm |
| Holding power steel | 24 hrs |
| Tensile strength | 90 N/cm |
| Initial tack | 7 cm |
| Elongation | 10 % |
| Temp. resistance | +120°C for 60 min |

STORAGE

Clean and dry in a well ventilated area, preferably at a temperature of 23°C.

Disclaimer: The above information is given in good faith, but the user should insure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. ATS All Tape Supplies cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications. Please take care when using this product on untreated aluminium and copper as it could leave adhesive residues on these substrates.

information_sales@alltape.eu

www.alltape.eu